

Toning Series Specification


DS554RGB

48V-12mm





【General description】

- 40m long strip driven by one end power supply with the same brightness from end to end
- Strips is of lower current with 48V input, better for longer wire connection
- Ultra long application with less power feed joint, high cost efficiency for project system
- With life span over 36000H
- Ta: -25-40°C; Tc: 75°C (max)



【Dimension】

- | | |
|------------------------------------|-------------------------------------|
| Input voltage: DC48V | Max.length: 40000mm(131.2') |
| CRI: / | Cutting unit: 9leds/166.66mm(6.56") |
| Max.power: 11.2W(1m) | LED pitch: 18.52mm(0.73") |
| Power range: 8.6~11.2W(1m) | Min. bend diameter: Φ60mm(2.36") |
| Rated current: 0.21A(1m) 8.4A(40m) | Mounting: 3M tape |
| Typical Power: 10W(1m) 400W(40m) | Copper foil: 4oz |
| tape IP: IP20/IP65/IP67 | |
| On-off times: 10000 (test times) | |
| Warranty: 5years | |




【Photo-electric Parameters】




CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
/	R	R:620-625nm	70	21	22	/
/	G	G:520-525nm	195	59	60	/
/	B	B:455-460nm	40	12	13	/
/	RGB	/	300	91	31	/

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/1mterter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.






【IP process information】



【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO		不防水	12mm*2.1mm	RGB	100%
NA		纳米防水	12mm*2.1mm	RGB	98%
ET		全包空心挤出防水	14mm*4.8mm	RGB	88%

【Accessories Information】

Name	Picture	Code	coding	description
Fixed Clip		94-02-00-0004	FSW12SA	Silicone clip, screw: PA 3*8mm, suitable for 12mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0048	DT12EA-A	Silicone plug kit, suitable for 12mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0049	DW12EA-A	Silicone tail plug kit, suitable for 12mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0026	CPT12EA-16100100	Transparent PVC mounting groove,suitable for 12mm FPC,silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel,suitable for ET/EF/EG/ERG waterproof LED strip

【Packing】

General customized package




IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	40000*12*2.1	40	400	1.355	13.55	14.9	41*41*26
NA	40000*12*2.1	40	400	1.362	13.62	15	41*41*26

Remark: data with 10% tolerance

· Engineering packaging of ET(IP67)

(free-soldering end caps with 40 cover per box could be ordered separately if needed)



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
ET	40000*14*4.8	40	80	4.046	8.092	8.557	25.5*25.5*26

【Precautions】

- Please drive the led strip with 48VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25℃~40℃. Storage temperature: 0℃~60℃. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.